

第 5 章 問 28

次のコマンド出力の結果を得るための **debug** コマンドはなんですか。次の選択肢から 1 つ 選んでください。

```
*Mar  2 14:54:16.691: TCP0: state was LISTEN -> SYNRCVD [23 ->
172.27.178.130(11002)]
*Mar  2 14:54:16.691: TCP0: Connection to 172.27.178.130:11002, received MSS 536,
MSS is 516
*Mar  2 14:54:16.695: TCP: sending SYN, seq 1873003733, ack 3597712450
*Mar  2 14:54:16.695: TCP0: Connection to 172.27.178.130:11002, advertising MSS 536
*Mar  2 14:54:16.695: TCP0: state was SYNRCVD -> ESTAB [23 ->
172.27.178.130(11002)]
*Mar  2 14:54:16.699: TCB82E0289C setting property TCP_TOS (11) 824CAFAC
*Mar  2 14:54:29.677: TCP66: state was ESTAB -> FINWAIT1 [23 ->
172.27.178.130(11002)]
*Mar  2 14:54:29.677: TCP66: sending FIN
*Mar  2 14:54:29.681: TCP66: state was FINWAIT1 -> FINWAIT2 [23 ->
172.27.178.130(11002)]
*Mar  2 14:54:29.681: TCP66: FIN processed
*Mar  2 14:54:29.681: TCP66: state was FINWAIT2 -> TIMEWAIT [23 ->
172.27.178.130(11002)]
*Mar  2 14:55:29.684: TCP66: state was TIMEWAIT -> CLOSED [23 ->
172.27.178.130(11002)]
*Mar  2 14:55:29.684: TCB 0x82E0289C destroyed
```

- A) **show ip tcp**
- B) **debug ip tcp**
- C) **debug ip tcp transactions**
- D) **debug ip tcp events**